

DBL Series

T5 LINKABLE BATTENS WITH A SWITCH

LINKABLE SLIMLINE FLUORESCENT SYSTEM

The compact design enables it to be installed in the most difficult and hard to light areas in display cases and under shelf applications. Integrated connecting system enables the provision of continuous and uniform lighting in the narrowest of spaces. Snap-in mounting clips make installation extremely easy. Each module is supplied with main power cord and interlinking cable (to enable module to module connection around corners). A state of the art T5 lamp, plus diffuser and mounting clips are also included. Fittings come standard with GE lamps. Maximum in series (from power cord): 8 Watt : 16 Units, 14 Watt : 10 Units, 21 Watt : 8 Units, 28W : 6 Units.

FEATURES

- SLIMLINE DESIGN ONLY 22 MM WIDE AND 44MM HIGH (WITH DIFFUSER)
- EASY INSTALLATION WITH QUICK-FIT CLIPS AND CABLE
- LONG LIFE OSRAM T5 COOL WHITE (4000K)
- OPTIONAL 3000K AND 6500K LAMPS ARE AVAILABLE ON REQUEST
- ELECTRONIC BALLAST FOR LOW POWER CONSUMPTION AND FLICKER FREE OPERATION
- SUPPLIED WITH DIFFUSERS WHICH MAY BE REMOVED AS REQUIRED
- SUPPLIED WITH 180MM JOINING CARD FOR CONNECTING AT ANGLES

LINKABLE T5 FITTINGS: COMPLETE KIT

DBL8C 8 Watt, Length 340mm
DBL14C 14 Watt, Length 640mm
DBL21C 21 Watt, Length 910mm
DBL28C 28 Watt, Length 1210mm

DBLK300 Linking Cord 300mm



ALL COMPLETE WITH DIFFUSER, MOUNTING CLIPS, POWER CORD & COOL WHITE LAMP

ENVIROBRIGHT Lighting Solutions

www.envirobright.com.au

Ph: 08 8370 9309 Fax: 08 8370 9304 Mob: 0412 083 484 Email: sales@envirobright.com.au