



RECESSED METAL HALIDE D/C RANGE

FEATURES

- SMR 70/SMR 150
- Metal halide shoplighters are a cost effective way of providing light with accurate colour rendering, for retail display areas, kit version includes lamp and remote control gear
- Adjustable lens

OPTIONS

- 70Watt
- 150Watt
- Silver or white


APPLICATIONS

- Display areas of retail stores
- General retail stores

DIMENSIONS(unit:mm)

- Cut out 210x12.5
- D:230x150
- H:130

POLAR CURVE



UTILISATION FACTOR TABLE

		LOR: 88.2%		SHR NOM: 1.78: 1.0				SHR MAX: 1.78: 1.0			
Reflectance		Room Index (K)									
		0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
Ceiling	Walls	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00
0.70	0.50	0.20	0.33	0.41	0.45	0.52	0.59	0.69	0.81	0.82	0.85
0.70	0.30	0.20	0.27	0.35	0.40	0.44	0.49	0.53	0.56	0.59	0.63
0.70	0.10	0.20	0.23	0.32	0.36	0.40	0.45	0.49	0.52	0.55	0.59
0.50	0.50	0.20	0.31	0.39	0.43	0.48	0.50	0.53	0.56	0.59	0.61
0.50	0.30	0.20	0.28	0.34	0.38	0.42	0.47	0.50	0.52	0.55	0.58
0.50	0.10	0.20	0.22	0.31	0.35	0.37	0.43	0.45	0.46	0.53	0.58
0.30	0.50	0.20	0.29	0.37	0.40	0.43	0.47	0.50	0.52	0.55	0.57
0.30	0.30	0.20	0.25	0.37	0.40	0.43	0.47	0.50	0.52	0.55	0.57
0.30	0.10	0.20	0.22	0.30	0.34	0.37	0.41	0.45	0.47	0.50	0.53
0.00	0.00	0.00	0.19	0.27	0.31	0.32	0.38	0.41	0.43	0.48	0.48
Distribution Factors	Floor	0.19	0.23	0.28	0.30	0.35	0.38	0.40	0.43	0.46	
	Walls	0.30	0.35	0.31	0.28	0.23	0.20	0.18	0.15	0.13	
	Ceiling	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08	0.08

DIMENSIONS

